## FLEXOTRAP MODULES







### Flexotrap M1

- **1** 60 x 120 cm / 23.6" x 47.2"
- 2 70 cm / 27.5" incl. wheelbase
- 3 Approx. 150 kg / 330 lbs
- Up to 25,000 shots\*



1 Bullet Trap Area

\* Depending on ammunition impact area, and distance.

2 Depth 3 Weight

Capacity

140 x 314 cm / 55.1" x 123.6" 2 60 cm / 23.6" 3 Approx. 1,000 kg / 2,204 lbs Up to 100,000 shots\*

Flexotrap H1

- 140 x 164 cm / 55.1" x 64.5"
- 2 60 cm / 23.6"
- 3 Approx. 400 kg / 882 lbs
- 4 Up to 100,000 shots\*



## Key Features

- Container Format (20-foot shipping container)
- Shielding that folds and assembles for transport
- ✓ Ability to mount targets and acoustic sensors
- ✓ Transportable and easily installed using a crane truck

. . . . . . .

.....

- ✓ Can be used as either a stationary or mobile range
- ✓ Infinitely scalable in width
- 🖌 Width: 11.50 m / 37' 9"
- Depth: 2.55 m / 8' 4"
- 🔗 Weight: 9,050 kg / 19.95k lbs





### Flexotrap L1

- 140 x 164 cm / 55.1" x 64.5"
- **2** 60 cm / 23.6" 3 Approx. 700 kg / 1,543 lbs
- Up to 100,000 shots\*
- 140 x 164 cm / 55.1" x 64.5" 2 60 cm / 23.6"

### 3 Approx. 950 kg / 2,094 lbs Up to 100,000 shots\*

Flexotrap D1



140 x 164 cm / 55.1" x 64.5"

Flexotrap D1-BMG

- 3 Approx. 1,400 kg / 3,086 lbs
- 4 The value is subject to variation



# 3

metal.

П

# Shooting Capabilities

Supports shooting up to 300 meters with a rifle and up to 50 meters with a pistol.

Operates in extreme conditions, withstanding temperatures as low as -40°C.



Recycling of projectile fragments and lead dust, generating revenue.

Prevents soil and groundwater contamination from lead and



## Scalability and Flexibility

Infinite scalability for various range configurations, both indoor and outdoor.

Transportable in standard format with reconfigurable options for diverse needs.

## 4

### Innovative Technology

Angled grids trap projectiles and collect fragments in a bottom container.

Reversible, interchangeable grids for easy maintenance and material efficiency.

No need for external power supply.